

GENUINE COMFORT

DELIVERING COMFORT CONSISTENTLY

Thru-Wall Air Conditioner | Spec Sheet | 24.25" W x 14.5" H x 20" D


Features

- Universal Thru-Wall Size
- Fits Universal Sized TTW Sleeves
- Digital Controls
- Remote Control Included
- UL Certified
- Slide-Out Washable & Easy-Clean Filter
- 24-Hour Programmable Timer
- Dehumidify Mode
- Trim Piece Included
- **Genuine Care Warranty:**
1 Year Unit Replacement

Product Photo




Wall Sleeve Dimensions



Model Identification

GC	—	Genuine Comfort
TTW	—	Thru The Wall
10	—	BTU Capacity
C	—	Cool Only; E for Electric Heat
R	—	Remote Included
A1	—	A1 = 115V; A2 = 230V

Wall Receptacles



For More Information, Please Contact:
(204) 201-0717 // 1-(866) 233-4022
info@genuinecomfort.com
or visit www.genuinecomfort.com

GENUINE COMFORT

DELIVERING COMFORT CONSISTENTLY

Thru-Wall Air Conditioner | Spec Sheet | 24.25" W x 14.5" H x 20" D

GC THRU WALL AC 115v			SPECIFICATIONS	
Model #			GCTTW-10CRA1	GCTTW-12CRA1
BTU			10,000	12,000
Control Type			Electronic	Electronic
Certificate			UL	UL
Power Supply		Ph-V-Hz	115V - 60Hz	115V - 60Hz
Cooling	RATED Capacity	Btu/h	10,000	12,000
	RATED EER	Btu/w.h,w/w	3.11	3.08
	RATED CEER	Btu/w.h,w/w	10.6	10.5
	RATED Input	W	943	1142
	RATED Current	A	8.3	10.0
Heating	RATED Capacity	Btu/h	/	/
	RATED Input(Heater)	W	/	/
	RATED Current	A	/	/
Starting Current		A	35.4	45.6
Indoor Air Circulation (Lo/Hi)		m3/h	346 / 458	487
Outdoor Air Circulation (Lo/Hi)		m3/h	440 / 635	595 / 715
Indoor Noise Level Db (Lo/Hi)		dB(A)	53 / 57	55 / 60
Outdoor Noise Level Db (Hi)		dB(A)	66	67
Operation Temp (Indoor)		°C - °C	17 - 32	17 - 32
Operation Temp (Outdoor)		°C - °C	18 - 43	18 - 43
Dimensions (WxDxH)		inch	24.21 x 20.28 x 14.53	24.21 x 20.28 x 14.53
Packing Dimensions (WxDxH)		inch	27.95 x 26.57 x 16.93	27.95 x 26.57 x 16.93
Net / Gross Weight		lbs	68 / 80	77 / 90
Plug Type		/	LCDI(5-15P)	LCDI(5-15P)
Refrigerant Type		/	R410A	R410A
Design Pressure		psi	300 / 520	300 / 520
Loading Capacity (40HQ)		SET	306	306

GC THRU WALL AC 230v			SPECIFICATIONS			
Model #			GCTTW-10CRA2	GCTTW-12CRA2	GCTTW-14CRA2	GCTTW-12ERA2
BTU			10,000	12,000	14,000	12,000
Control Type			Electronic	Electronic	Electronic	Electronic
Certificate			UL	UL	UL	UL
Power Supply		Ph-V-Hz	230/208V - 60Hz	230/208V - 60Hz	230/208V - 60Hz	230/208V - 60Hz
Cooling	RATED Capacity	Btu/h	10,000	12,000	14,000	12,000
	RATED EER	Btu/w.h,w/w	3.11	3.08	2.73/2.78	2.78
	RATED CEER	Btu/w.h,w/w	10.6	10.5	9.3	9.5
	RATED Input	W	943	1142/1114	1505/1431	1263/1232
	RATED Current	A	4.5	5.2/5.6	6.9/7.5	5.5/5.9
Heating	RATED Capacity	Btu/h	/	/	/	10600/8600
	RATED Input(Heater)	W	/	/	/	3450/2821
	RATED Current	A	/	/	/	15/13.5
Starting Current		A	19.5	21.3	37.5	16.5
Indoor Air Circulation (Lo/Hi)		m3/h	356 / 468	400 / 472	430 / 503	409 / 487
Outdoor Air Circulation (Lo/Hi)		m3/h	440 / 635	651 / 798	614 / 727	595 / 715
Indoor Noise Level Db (Lo/Hi)		dB(A)	56 / 59	58 / 61	59 / 61	56 / 60
Outdoor Noise Level Db (Hi)		dB(A)	67	67	69	68
Operation Temp (Indoor)		°C - °C	17 - 32	17 - 32	17 - 32	17 - 32
Operation Temp (Outdoor)		°C - °C	18 - 43	18 - 43	18 - 43	18 - 43
Dimensions (WxDxH)		inch	24.21 x 20.28 x 14.53	24.21 x 20.28 x 14.53	24.21 x 20.28 x 14.53	24.21 x 20.28 x 14.53
Packing Dimensions (WxDxH)		inch	27.95 x 26.57 x 16.93	27.95 x 26.57 x 16.93	27.95 x 26.57 x 16.93	27.95 x 26.57 x 16.93
Net / Gross Weight		lbs	69 / 80	76 / 87	75 / 86	78 / 89
Plug Type		/	LCDI(6-15P)	LCDI(6-15P)	LCDI(6-15P)	LCDI(6-20P)
Refrigerant Type		/	R410A	R410A	R410A	R410A
Design Pressure		psi	300 / 520	300 / 520	300 / 520	300 / 520
Loading Capacity (40HQ)		SET	306	306	306	306